



| Job Demand Analysis | | | | |
|--------------------------|--|--|--|--|
| Placement/Job Title: | Plant Operators – Works Services | | | |
| Division/Branch: | Technical Services / Works Services | | | |
| Date of Assessment: | 28 November 2012 | | | |
| Assessment Completed By: | Human Resources Advisor 2 Works Supervisor | | | |
| Standard Hours: | 7am to 4pm (8½ hours per day), 9 day fortnight | | | |
| Variable Hours: | X Overtime | | | |
| Breaks / Rest Periods: | 15 minute morning tea 30 minute lunch | | | |

Environmental/Psychosocial Factors

The Plant Operators operate specific plant items including the backhoe, roller, loader, excavator, skidsteer and tractor. They work in gangs. Most of their time is spent inside operating the plant but the plant operator may be required to perform labouring tasks with the crew if plant operating duties are not required.

Tasks such as road patching need to be completed within the allocated time frame to allow minimum disruption to traffic flow.

Concentration and care needs to be taken when operating plant in relation to the surrounding areas to avoid tipping the machine.

Job Descriptions

Plant operators are responsible for providing skilful operation of specialised equipment in the provision of civil engineering services to the city of Dubbo.

Please see relevant position description for further information.

| Physical Demands | Rarely 1-5% | Occasional 6-33% | Frequent 34-66% | Continuous 67-100% | Comments |
|---------------------|----------------|---------------------|--------------------|-----------------------|--|
| Standing | | X | | | Required when performing labouring tasks. |
| Walking | | Х | | | Required when performing labouring tasks and may include rough and/or inclined ground surfaces. |
| Sitting | | | | Х | Prolonged sitting is required to operate foot and hand controls - includes levers, joy sticks, switches, steering wheel and pedals. The seat is adjustable in height and the backrest can be altered for added support. Air suspension is available in the seat. However, some |

| Physical | Rarely | Occasional | Frequent | Continuous | Comments |
|---------------------|--------|------------|----------|------------|---|
| Demands | 1-5% | 6-33% | 34-66% | 67-100% | iousing and vibration may be |
| | | | | | jarring and vibration may be |
| | | | | | experienced, depending on the road surface. |
| Climbing | | | X | | Access to the cabin is gained |
| ladders, | | | ^ | | by three steps (commencing at |
| stairs or | | | | | knee level) and a handle |
| scaffolding | | | | | located at head level. Climbing |
| Joannolaing | | | | | is also required when greasing |
| | | | | | the machine. |
| Bending / | | Х | | | May be required for labouring |
| Stooping | | | | | tasks and when replacing |
| | | | | | cutting edges on the machine. |
| | | | | | The worker also has to bend |
| | | | | | forward to rotate the seat and |
| | | | | | to separate the foot pedals for |
| | | | | | extra control of the machine at |
| | | | | | times. |
| Squatting / | | X | | | May be required for labouring |
| Crouching | | | | | tasks and when replacing |
| 17 | | | | | parts on the machine. |
| Kneeling | | Χ | | | May be required for labouring |
| | | | | | tasks and when replacing |
| Danahina | | V | | | parts on the machine. |
| Reaching | | Х | | | Overhead reach is required |
| overhead | | | | | when using the handle to assist with transfers into the |
| | | | | | cabin. The two way radio is |
| | | | | | also located at shoulder height |
| | | | | | within the cabin. |
| Reaching at | | | | Х | Repetitive bilateral shoulder |
| waist level or | | | | | flexion and upper limb reach is |
| below | | | | | required to hold and |
| | | | | | manoeuvre the steering wheel. |
| | | | | | Repetitive bilateral upper limb |
| | | | | | flexion, abduction and external |
| | | | | | rotation are also required to |
| | | | | | access and operate the |
| | | | | | controls. |
| Trunk | | | | X | Repetitive trunk and neck |
| Rotation | | | | | rotation is required to assist |
| | | | | | with visibility and two exterior |
| | | | | | mirrors are also available for |
| Donotitivo | | | | X | use by the worker. Bilateral fine motor actions are |
| Repetitive Forearm, | | | | ^ | required to conduct the pre- |
| hand and | | | | | check of the Plant and to |
| finger | | | | | operate the numerous controls |
| movement | | | | | within the cabin (located to |
| | | | | | each side of the worker). The |
| | | | | | worker uses a cylindrical grip |
| | | | | | on the joy stick, along with |
| | | | | | repetitive finger and thumb |
| | | | | | movements. |
| Manual | | | | Х | Bilateral upper and lower limb |
| dexterity and | | | | | actions are required to operate |

| Physical Demands | Occasional 6-33% | Continuous 67-100% | Comments |
|---------------------|---------------------|-----------------------|---|
| handling | | | the machine. Lower limb force is also required through the pedals at times to stop the machine veering to one side. |

| Manual Handling | | | | |
|-----------------|---------|------------|--|--|
| | Weight: | Frequency: | Comments: | |
| Lifting | 15-20kg | Occasional | Lifting of cement bags and tools/equipment may be required on an intermittent basis when performing labouring tasks. | |
| Carrying | 15-20kg | Occasional | Carrying of cement bags and tools/equipment over short distances may be required on an intermittent basis when performing labouring tasks. | |
| Pushing/Pulling | 30-40kg | Rare | Push/pull of the cutting blades may be required to position them for placement of nuts. | |

| Tools Used | | |
|-------------------|---------|---|
| Tool: | Weight: | Comments: |
| Blades | 30-40kg | Blades need to be manoeuvred slightly to position and secure to |
| | | the machine. |
| Cement | 15kg | May be lifted and carried over short distances. |
| Chains | 15kg | May be lifted and carried over short distances. However, a |
| | | labourer usually performs this task. |
| Shovel | 2kg | May be used to move a variety of substances such as dirt and |
| | | gravel. |
| Broom | 2kg | Used to clear the road and gutters as required. |
| Stop/go sign | 2-3kg | Cylindrical grip and static holding of the sign is required. |
| Hand tools | < 1kg | An assortment of hand tools may be used. |
| Power Tools | 2-3kg | Used during labouring tasks |
| Chainsaw | 15kg | Used during labouring tasks |
| GPS Device | < 1kg | Handheld GPS device |

| Balance | | |
|------------------------------------|--------------|--|
| | Exposure to: | Comments: |
| Level ground | Yes | When walking on prepared road |
| | | surfaces. |
| Uneven ground | Yes | When walking on unprepared road |
| | | surfaces and when performing labouring |
| | | tasks. |
| Unprotected heights or high levels | Yes | Includes access to/from the Plant cabin. |

| Environmental Conditions | | |
|---------------------------------|--------------|--|
| | Exposure to: | Comments: |
| Inside work | Yes | The worker performs the majority of |
| | | tasks whilst sitting in the Plant cabin. |

| Environmental Conditions | | |
|--|--------------|---|
| | Exposure to: | Comments: |
| Outside work | Yes | The worker may be required to perform labouring tasks with the crew when not operating Plant. |
| Night Work | Yes | Occasionally |
| Extreme heat | Yes | The worker may be exposed to the environment when performing labouring tasks. |
| Extreme cold | Yes | The worker may be exposed to the environment when performing labouring tasks. |
| Humid or wet | Yes | The worker may be exposed to the environment when performing labouring tasks. |
| Noise | Yes | Noise is reported to be minimal within the Plant cabin. |
| Vibration | Yes | Some vibration is experienced when travelling over rough surfaces. |
| Mechanical hazards | Yes | The worker has to be aware of surrounding traffic and plant machinery. |
| Electrical hazards | Yes | The worker has to be aware of overhead lines, underground power and water lines and other electrical hazards. |
| Risk of burns | Yes | When checking engine, hot exhaust, engine |
| Radiant energy | Yes | |
| Poor ventilation | Yes | Trench work |
| Moving objects | Yes | Includes other plant machinery and general traffic flow. The worker must also be aware of the position of the bucket and boom at all times. |
| Sharp tools | Yes | Chainsaw |
| Cluttered or slippery floors | Yes | The steps into the cabin may be slippery at times, especially if working in a muddy area. |
| Elevated surfaces | Yes | Access to/from the Plant cabin and when performing pre-start checks of the machine. |
| Lighting | Yes | When required, sufficiently supplied |
| Exposure to fumes/odours/ dusts/mists/gases | Yes | The worker may be exposed to traffic fumes when driving and labouring. |
| Exposure to biological hazards | Yes | Sharps |

| Sensory/Communication | | |
|-----------------------|-----------|---|
| | Required: | Comments: |
| Vision | Yes | High levels of visual perception are required when operating the machine so that the operator is aware of other traffic and hazards. This may involve twisting the neck on a repetitive basis to gain visual information. |
| Hearing | Yes | General liaison with other workers. |
| Speech | Yes | General liaison with other workers. |
| Reading | Yes | Completion of paperwork as required. |

| Writing | Yes | Completion of paperwork as required. |
|-------------------|-----|---------------------------------------|
| Numerical ability | Yes | The worker needs to be aware of depth |
| | | when digging holes. |

This Job Demand Analysis has been assessed and approved by the relevant Supervisor and corresponding Manager within Dubbo City Council. This Job Demand Analysis will be implemented on 8 April 2013.